WESDOME

PRESS RELEASE

DRILLING RESULTS – VC ZONE, KIENA COMPLEX

Val-d'Or, Quebec, June 1, 2005 – Further underground drilling results have been received from the VC zone at the Company's wholly owned Kiena Complex. Delineation drilling of the easternmost section (13230E) is complete. As expected, the zone becomes thinner at this section. The results are tabulated below. All holes are drilled from the 520 metre level with true north azimuths.

SIGNIFICANT INTERSECTIONS

SECTION 13230E

Hole #	Dip (°)	From (m)	To (m)	Corelength (m)	True Width (m)	Assay (g/t)	Cut Assay (g/t) *	Zone
U-3775	+73	77.8	83.0	5.28	3.5	8.25	8.25	VC3
		88.0	89.0	1.0	0.9	15.70	15.70	VC2
		104.0	109.2	5.2	4.0	0.84	0.84	VC1
U-3776	+46	48.0	49.6	1.6	1.4	10.70	10.70	VC3
		65.1	66.1	1.0	0.9	7.55	7.55	VC2
		78.3	82.3	4.0	3.7	21.51	15.10	VC1
U-3777	+24	55.0	55.5	0.5	0.5	6.05	6.05	VC2
		81.4	85.4	4.0	4.0	4.29	4.29	VC1
U-3778	+03	1.2	4.6	3.4	3.3	3.00	3.00	VC4
U-3779	-48	12.0	13.5	1.5	1.0	3.60	3.60	VC4
		98.2	99.7	1.5	1.0	3.50	3.50	VC2
		124.0	125.0	1.0	0.7	1.65	1.65	VC1

* Assays cut to 34.28 gAu/tonne

Infill drilling on sections 13200E and 13215E is also complete. This drilling confirms the continuity of the zone and indicates that the zone is open at depth. The results are tabulated below. Previous results from sections 13200E and 13215E are tabulated in press releases dated March 4, 2005 and April 6, 2005. Results from sections 13170E and 13185E are tabulated in press releases dated Dec. 15, 2004, Jan. 19, 2005, and Feb. 16, 2005.

Mine d'Or Wesdome Inc.
950, Chemin Kienawisik, C.P. / P.O. Box 268
Val-d'Or, Qc., J9P 4P3
Tel: (819) 738-4031 Fax: (819) 738-5452

Wesdome Gold Mines Inc.
8 King Street East, Suite 1305
Toronto, Ontario M5C 1B5
Tel: (416) 360-3743 Fax: (416) 360-7620
E-mail: rivgold@idirect.ca

SECTION 13200E

Hole #	Dip (º)	From (m)	To (m)	Corelength (m)	True Width (m)	Assay (g/t)	Cut Assay (g/t) *	Zone
U-3790	+81	95.0	98.0	3.0	2.0	5.45	5.45	VC3
		105.0	110.7	5.7	4.0	9.44	8.91	VC2
U-3791	+65	63.5	72.5	9.0	5.5	7.45	6.26	VC3
		82.5	83.7	1.2	1.0	15.05	15.05	VC2
		92.2	93.1	0.9	0.7	18.65	18.65	VC2
		101.0	112.6	11.6	10.0	4.14	4.14	VC1
U-3792	+53	46.1	50.0	3.9	3.9	8.74	8.74	VC3
		66.4	68.3	1.9	1.9	15.24	15.24	VC2
		100.0	102.4	2.4	2.4	5.61	5.61	VC1
U-3793	-16	43.8	58.0	14.2	11.0	9.70	6.030	VC3
		61.6	68.0	6.4	4.0	2.45	2.45	VC2
U-3794	-37	61.0	68.5	7.5	5.0	5.34	5.34	VC3
		101.9	103.5	1.6	1.4	16.50	16.50	VC2
		115.0	119.5	4.5	4.0	6.14	6.14	VC1
U-3795	-48	0.5	3.0	2.5	1.0	5.30	5.30	VC4
		107.0	110.0	3.0	1.5	3.20	3.20	VC3
		140.0	143.5	3.5	1.6	3.75	3.75	VC2
		146.9	151.5	4.6	2.3	3.00	3.00	VC1

SECTION 13215E

Hole #	Dip (º)	From (m)	To (m)	Corelength (m)	True Width (m)	Assay (g/t)	Cut Assay (g/t) *	Zone
U-3796	+74	66.0	73.1	7.1	4.2	6.83	6.83	VC3
		83.0	103.5	20.5	12.5	7.74	7.74	VC2
		117.0	125.0	8.0	4.8	3.65	3.65	VC1
U-3797	-08	47.0	62.3	15.3	12.7	13.41	9.51	VC3+VC2
U-3798	-30	63.5	65.5	2.0	1.2	5.63	5.63	VC3
		93.0	94.0	1.0	0.7	5.05	5.05	VC2
U-3799	-43	142.0	150.7	8.7	6.2	5.33	5.33	VC2
U-3800	-47	152.0	160.0	8.0	6.0	2.34	2.34	VC2

* Assays cut to 34.28 gAu/tonne

The VC zone consists of an en-echelon series of at least three mineralized zones which, to date, have been traced downdip for over 500 metres and along strike for 60 metres. The zone remains open at depth and to the west. Mineralization consists of silicified and albitized breccia hosted in basalt within a basalt-komatiite sequence cut by minor intermediate to felsic intrusive bodies.

The drill has been removed in order to extend the drilling drift to the west. This will enable us to extend the drilling westward. The westernmost section drilled to date, section 13170E, included intersections of 29.5 metres of 4.28 gAu/tonne, 29.4 metres of 6.01 gAu/tonne and 10.1 metres of 7.0 gAu/tonne in the VC2 zone and intersections of 9.4 metres of 9.72 gAu/tonne, 16.8 metres of 13.27 gAu/tonne, 18.0 metres of 8.17 gAu/tonne, 30.0 metres of 6.30 gAu/tonne and 35.6 metres of 6.72 gAu/tonne in the VC3 zone (see press release dated February 16, 2005).

Assay work is conducted by commercial facility Bourlamaque Assay Laboratories in Val-d'Or, Quebec, employing conventional fire assay techniques on one assay ton sample aliquots. Core samples with visible gold are analyzed by metallic sieve methods on 500 gram aliquots. Samples returning assays greater than 5.0gAu/tonne are checked using conventional fire assay techniques. Samples returning assays greater than 15.0gAu/tonne are checked using metallic sieve methods. Check assay work is conducted by commercial facility Techni-Lab S.G.G Abitibi Inc. in Sainte-Germaine-Boulé, Quebec. George Mannard, P.Geo. and "Qualified Person" as per NI 43-101, has prepared and verified the content of this release.

Wesdome Gold Mines Inc. trades on the TSX-V Exchange under the symbol "WDG" and has 43.5 million shares outstanding.

For further information and previous press releases please visit:
www.wesdomegoldmines.com
or contact:

Paul Cregheur, President **or** **Murray Pollitt, Chairman**
at: 819-738-4031 x 5361 **at: 416-803-2304**

The TSX Venture Exchange has not reviewed and does not accept responsibility for the adequacy or accuracy of this release or the information contained herein.